

UNITÀ CASSETTE AD ACQUA
WATER CASSETTE



CWPS

UNITÀ CASSETTE AD ACQUA
WATER CASSETTES



- Disponibile in **12 modelli**.
- Struttura portante in **lamiera di acciaio zincato** isolata internamente di dimensioni compatibili con i controsoffitti standard.
- Altezza contenuta in **solì 260mm** per i modelli piú piccoli.
- **Totale accessibilità dal basso**.
- **Filtro rigenerabile** ad alta efficienza.
- Pompa di scarico condensa estremamente silenziosa.
- Gruppo ventilante ad alta efficienza a **3 velocità**.
- Alette orientabili su **4 direzioni**.
- Disponibile nei modelli a **2 tubi e a 4 tubi**.
- Resistenze elettriche integrative.
- Presa d'aria esterna.
- Pannello di controllo a parete.
- Possibilità di inviare aria trattata in locali contigui



- Available in **12 sizes**.
- Structure in **galvanized steel** internally insulated with polyurethane material dimensions compatible with the standard false ceilings.
- The height of the unit is **only 260mm** for the smaller series.
- **Total accessibility from underneath**.
- **Long life** washable filter.
- Extremely low noise condensate pump.
- High efficiency fan group at **3 speeds**.
- Standard **4 ways air** discharge louvers.
- Available **2 pipe and 4 pipe** version.
- Additional electric heater.
- Fresh air inlet connection.
- Wired wall control panel.
- Branch duct connection.



CWPS

Unità a 2 tubi // 2 pipe system

Mod.			050	070	080	090	100	120	150
Pot. frigorifera totale Total cooling capacity	kW	MAX	2,58	3,41	4,83	5,45	7,25	8,39	10,55
Pot. frigorifera sensibile Sensible cooling capacity	kW	MAX	2,13	2,72	3,50	4,19	5,51	6,01	7,65
Pot. termica Heating capacity	kW	MAX	3,22	4,35	5,70	6,42	9,17	10,95	13,87
Portata aria Air flow	m³/h	MAX	500	750	800	910	1000	1270	1550
Pressione sonora Sound pressure level	dB(A)		31	31	32	32	34	46	37
Alimentazione Power supply	V/Ph/Hz		230/1/50						
Dimensioni unità/griglia Unit/grill dimensions	mm		570x570x250 / 620x620x30				1170x570x250 / 1220x620x30		
Conessioni acqua Water connections	"		3/4 F						

CWPS

Unità a 4 tubi // 4 pipe system

Mod.			054	084	094	124	154
Pot. frigorifera totale Total cooling capacity	kW	MAX	2,90	3,65	4,47	6,52	7,45
Pot. frigorifera sensibile Sensible cooling capacity	kW	MAX	2,26	2,76	3,34	4,97	5,83
Pot. termica Heating capacity	kW	MAX	3,48	4,43	5,21	7,65	10,36
Portata aria Air flow	m³/h	MAX	570	800	950	1270	1550
Pressione sonora Sound pressure level	dB(A)		31	32	34	36	37
Alimentazione Power supply	V/Ph/Hz		230/1/50				
Dimensioni unità/griglia Unit/grill dimensions	mm		570x570x250 / 620x620x30			1170x570x250 / 1220x620x30	
Conessioni acqua Water connections	"		3/4 F				



Rese frigorifere

- Temperatura ambiente: 27°C 47%
- Temperatura acqua: 7/12°C
- Massima velocità

Rese termiche:

- Temperatura ambiente: 20°C
- Temperatura acqua: 70/60°C

**Pressione sonora misurata
ad 1 mt. di distanza**

Cooling:

- Room temperature: 27°C 47%
- Water temperature: 7/12°C
- Max speed

Heating:

- Room temperature: 20°C
- Water temperature: 70/60°C

**Sound pressure level measured
at 1 mt distance from the fan**

